


Fall Protection Inspection Checklist

Harness Number _____



Harness and Body Belt Inspection Criteria

| | Pass/Fail | | Pass/Fail |
|--|-----------|--|-----------|
| Webbing Frayed edges Broken fibers Pulled stitches Cuts Burns Chemical damage | | Tongue Buckles Distortion in shape and motion Overlap buckle frame Move freely back and forth Roller turns freely Sharp edges Heavy wear from use | |
| D-Rings/Back Pads (D-Ring should pivot freely) Distortion Cracks Breaks Rough or sharp edges | | Friction and Mating Buckles Distortion Bars must be straight (Special attention to corners and attachment points of the center bar) | |
| Attachment of Buckles Unusual Wear Frayed Cut Fibers Distortion of buckles or D-rings | | Grommets Loose Distorted Broken Additional punched holes | |

Lanyard Number _____

Lanyard Inspection Criteria

| | Pass/Fail | | Pass/Fail |
|---|---|---|-----------|
| Steel While rotating the steel lanyards <ul style="list-style-type: none"> Cuts Frayed areas Unusual wearing Broken strands | | Rope Rotate rope while inspecting from end to end <ul style="list-style-type: none"> Fuzzy Worn Broken or cut fibers Rope diameter uniform Splice should not have loose or cut strands | |
| Web While bending webbing over a pipe, observe each side <ul style="list-style-type: none"> Cuts Broken Fibers Burns | <ul style="list-style-type: none"> Discoloration Cracks Swelling Chemical Damage Pulled Stitches | Shock Absorber Pack <ul style="list-style-type: none"> Burns, tears, rips or loose strands Signs of deployment Deterioration Stitching | |

Snap Inspection Criteria (Hardware)

| | Pass/Fail | | Pass/Fail |
|---|-----------|--|-----------|
| Snaps Hook and Eye Distortions <ul style="list-style-type: none"> Cracks Corrosion Pitted surfaces | | Keeper Spring Should exert sufficient force to firmly close keeper | |
| Keeper Seat into the nose without binding <ul style="list-style-type: none"> Distorted Obstructed | | Thimbles Must be firmly seated in the eye of splice <ul style="list-style-type: none"> Sharp Edges Distorted Cracks | |
| Keeper Locks Must prevent the keeper from opening when keeper closes | | | |

Inspector's Signature

Date